



CONSTRUKT FLOORING SPECIFICATIONS

PRODUCT INFORMATION

CONSTRUCTION	Solid format with 100% bamboo from top to bottom
PLANK DIMENSIONS	3-3/4" wide, 75-5/8" long, 5/8" thick
MILLING	4-sided micro-bevel / tongue & groove
FINISH	8-step Treffert [®] aluminum oxide finish
COLOR VARIANCE	Bamboo is a natural product, thus colors and tones may vary.
ADHESIVES	Dynea Prefere Adhesives. No added Urea Formaldehyde
INSTALLATION	Nail or glue. Radiant floor heating compatible On or above grade
HARDNESS	Janka Hardness Rating of 1200 - 1600
ENVIRONMENTAL	FSC Certified: FSC C020547 / E0 & CARB II Compliant Qualifies for LEED [®] Credits IEQ4.4, MR6, and MR7

PACKAGING

BOX WEIGHT: 48LBS	CONTAINER: 45 Boxes/Pallet	PALLETS / 40' CONTAINER: 20
PLANKS PER BOX: 12	SQFT PER BOX: 23.75	

WARRANTY


FINISH	50-year Residential / 5-year Light Commercial
STRUCTURE	Lifetime Structural Warranty

RESOURCES

Download the latest versions of our installation and maintenance guides, as well as watch installation videos, at www.bamboohardwoods.com




SMOOTH
HG BLONDE 55136N



SMOOTH
HG CARBONIZED 55138N



SMOOTH
VG BLONDE 55135N



SMOOTH
VG CARBONIZED 55137N

