



SUITE FLOORING SPECIFICATIONS

PRODUCT INFORMATION

CONSTRUCTION	100% solid strand bamboo from top to bottom
PLANK DIMENSIONS	3-3/4" wide, 72-3/4" long, 1/2" thick* or 5-5/8" wide, 72-3/4" long, 1/2" thick
MILLING	4-sided micro-bevel / tongue & groove
FINISH	8-step Treffert [®] aluminum oxide finish
COLOR VARIANCE	Bamboo is a natural product, thus colors and tones may vary.
ADHESIVES	Dynea Prefere Adhesives. No added Urea Formaldehyde
INSTALLATION	Nail or glue. Not radiant floor heat compatible On or above grade
HARDNESS	Janka Hardness Rating of 3,000+
ENVIRONMENTAL	FSC Certified: FSC C020547 / CARB II Compliant / LEED [®] Credits IEQ4.4, MR6, and MR7 / FloorScore [®] Certified

PACKAGING FOR 3-3/4" SIZE

BOX WEIGHT: 60LBS	CONTAINER: 55 Boxes/Pallet	PALLETS / 20' CONTAINER: 12
PLANKS PER BOX: 12	SQFT PER BOX: 22.95	

PACKAGING FOR 5-5/8" SIZE

BOX WEIGHT: 52LBS	CONTAINER: 63 Boxes/Pallet	PALLETS / 20' CONTAINER: 10
PLANKS PER BOX: 6	SQFT PER BOX: 22.95 or 16.96	PALLETS / 40' CONTAINER: 12

WARRANTY

FINISH	50-year Residential / 5-year Light Commercial
STRUCTURE	Lifetime Structural Warranty

RESOURCES

Download the latest versions of our installation and maintenance guides, as well as watch installation videos, at www.bamboohardwoods.com

*3-3/4" size to be phased out in 2017

