

INSPIRE PRO SPC

PRODUCT SPECIFICATIONS / TECHNICAL DATA

Styles:	Eclipse, Daybreak, Cascade, Sunrise, Sunset, Nightfall
Composition:	Phthalate-Free Stone Polyvinyl Chloride
Installation Method:	Unilin Licensed Click Locking System
Size (inches / mm):	7" x 48" (nominal)
Total Thickness:	5mm
Pre-Attached Underlayment:	1mm High Density IXPE Embossed
Wear Layer:	20mil (0.5mm)
Finish:	UV Coated, Nano-Silver Anti-Scratch Coating System
Texture:	Antique Wood
Edge:	Micro Bevel
Sq.Ft. / Piece:	2.364
Sq.Ft. / Box:	23.64
Pieces / Box:	10
Boxes / Pallet:	50
Weight / Pallet:	2150 lbs
Limited Warranty:	Lifetime Residential 15 Year Light Commercial
<u>TESTING</u>	
ASTM F1700 - Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements
ASTM E648 - Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)
ASTM D2047 - Coefficient of Friction (Slip Resistance)	Meets and exceeds passing requirements
ASTM F925 - Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM E492 - Impact Sound Insulation Acoustical Testing (IIC)	Exceeds over 54 IIC regulation : over 6" concrete
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements
<u>SUSTAINABILITY</u>	
Recycled Content:	No
ISO 9001 - Quality Management System:	Meets and exceeds passing requirements
ISO 14001 - Environmental Management System:	Meets and exceeds passing requirements
FloorScore® Certified:	Yes
GreenGuard Gold Certified:	Yes