

# PRODUCT SPECIFICATIONS / TECHNICAL DATA



## MEDITERRANEAN Series

SPC RigidCore

Styles:	Alexandria Timberstone, Valencia Travertine, Tripoli Limestone, Malaga Dolomite, Antalya Timberstone
Composition:	Phthalate-Free Stone Polyvinyl Chloride
Installation Method:	I4F Click System
Size (inches / mm):	12" x 24" (nominal)
Total Thickness:	5.5mm
Pre-Attached Underlayment:	1.5mm High Density IXPE Embossed
Wear Layer:	20mil (0.5mm)
Finish:	UV Coated, Aluminum Oxide Anti-Scratch Coating System
Texture:	Stone or Slate Texture
Edge:	Painted V-Groove Edge
Sq.Ft. / Piece:	2
Sq.Ft. / Box:	24.03
Pieces / Box:	12
Boxes / Pallet:	60
Weight / Pallet:	2549 lbs.
Limited Warranty:	Lifetime Residential 15yr. Light Commercial
<b>TESTING</b>	
ASTM F1700 - Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements
ASTM E648 - Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)
ASTM D2047 - Coefficient of Friction (Slip Resistance)	Meets and exceeds passing requirements
ASTM F925 - Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM E492 - Impact Sound Insulation Acoustical Testing (IIC)	Exceeds 54 IIC - over 6" concrete: Tested results of 68 IIC
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements
<b>SUSTAINABILITY</b>	
Recycled Content:	No
ISO 9001 - Quality Management System:	Meets and exceeds passing requirements
ISO 14001 - Environmental Management System:	Meets and exceeds passing requirements
FloorScore® Certified:	Yes
GreenGuard Gold Certified:	Yes

[www.dhockstein.com](http://www.dhockstein.com)

301-336-6600