

Super Muffler

PREMIUM HIGH DENSITY
ACOUSTIC PAD
IIC 78/STC 73 RATING

Specifically designed for commercial and residential vinyl and WPC plank flooring

* Can also be used with laminate and engineered flooring

Sound Qualities

- STC73 (ASTM E 989-12)
- IIC 78 (ASTM E 989-12)

Density

- 180kgs/m³

Vapor Barrier Strength

- Impermeable 0.11g/cm² (GB/T 328.10-2007)

Thickness

- 1.5mm

Appropriate Installation Methods

- Double Glue Down*
- Nail Down*
- Floating

Installation Instructions

- Push edges together, avoid overlapping
- Tape seams together if needed

Eco-friendly

- Zero VOC
- VOC shield, diminishes sub floor emissions
- Non-Phenol
- Exceeds all standards for indoor air quality
- No toxic additives

Hypo Allergenic and resistant to mold/mildew

Superior sound dampening quality



NOTE: When installing PHD for LVT in lower ground floors like basements or areas where a moisture barrier is required, spread out the underlayment 1" - 2" up the walls. New concrete should cure for 60-90 days minimum before installing. Check for excessive dampness before installation and refer to the flooring manufacturer's recommendations.

* Consult your flooring expert for additional instruction and to ensure proper adhesives, fasteners and installation methods are used.