



## 80/10 Best Specifications

Series	80/10
Nominal Total Thickness	0.80" (2.03 mm)
Wear Layer Thickness	0.010" (0.25 mm)
Wear Layer Finish	Urethane (Low Gloss)
Width	12' (3.6m)
Maximum Roll Size	149 sq. yd. (125 m2)
Weight per Sq. Yd.	2.82 lbs (1.30 kg)
ASTM F1303	Type I, Grade 3, Class C
ASTM D2047 (Slip)	>.5
ASTM E648 (Fire)	>.45 W/cm2
ASTM E662 (Smoke)	<450
ASTM F137 (Flexibility)	1/4" (6,4mm)
ASTM F925 (Stainng)	Excellent
ASTM F970 Static Load Limit	75 lbs./sq. in. (5.3 kg/cm2)
ASTM F1514 (Heat Stability)	E < 8
ASTM F1515 (Light Stability)	E < 8
ASTM E2179 (Impact Sound Reductions)	IIC 24 dB
Installation System	Glueless or full-spread (Mult-Family Applications)
Location	Below, on and above grade concrete, above grade plywood
Adhesive	Tarkett® QBond-One' or 959
Seam Sealer	Tarkett DT-65 Seam Sealer
HUD/FHA Minimum/HUD	Yes, =/>0.010' wear layer
Phthalate Free	Yes