



55/10 Better Specifications

Series	55/10
Nominal Total Thickness	0.053" (1.40 mm)
Wear Layer Thickness	0.010" (0.25 mm)
Wear Layer Finish	Urethane (Low Gloss)
Width	12' (3.6m)
Maximum Roll Size	205 sq. yd. (171 m ²)
Weight per Sq. Yd.	2.40 lbs (1.09 kg)
ASTM F1303	Type I, Grade 3, Class C
ASTM D2047 (Slip)	>.5
ASTM E648 (Fire)	>.45 W/cm ²
ASTM E662 (Smoke)	<450
ASTM F137 (Flexibility)	1/4" (6,4mm)
ASTM F925 (Stainng)	Excellent
ASTM F970 Static Load Limit	75 lbs./sq. in. (5.3 kg/cm ²)
ASTM F1514 (Heat Stability)	E < 8
ASTM F1515 (Light Stability)	E < 8
ASTM E2179 (Impact Sound Reductions)	IIC 16 dB
Installation System	Glueless or full-spread (Multi-Family Applications)
Location	Below, on and above grade concrete, above grade plywood
Adhesive	Tarkett® QBond-One' or 959
Seam Sealer	Tarkett DT-65 Seam Sealer
HUD/FHA Minimum/HUD	Yes, =/>0.010' wear layer
Phthalate Free	Yes