



**LX Hausys America, Inc.**

900 Circle 75 Parkway, Suite 1500  
 Atlanta, GA 30339  
 866-544-4622  
 www.lxhausysusa.com

LX HAUSYS FLOORS PRESTG GLUEDOWN SPECIFICATION		
<b>COLLECTION NAME</b>	Savana Dryback	
<b>INVENTORY STYLE #</b>		
<b>STYLE NAME(S)</b>		
<b>SELLING STYLE #(S)</b>	Savana Dryback	
<b>TOTAL # SKU'S(COLORS)</b>	6	
<b>PRODUCT SPECIFICATIONS / CONTENT / CERTIFICATIONS</b>	<b>DETAILS</b>	<b>ADDITIONAL INFORMATION</b>
Thickness	2.0mm (0.787 in)	
Wear Layer	12mil (0.3mm)	
Glass Fiber		
Finishing / Coating	Enhanced UV Urethane Coating	
Nominal Dimensions (inches)	6" x 48"	
Actual Dimensions (inches & mm)	150mm x 1200mm	
Micro-Beveled	No	
Class / ASTM F1700	Class III Printed Film vinyl tile - Type B(embossed)	
Backing Class	Commercial Grade	
Gloss Level	4~8	
Commercial Traffic	Light Commercial	
Added Antimicrobial	No	
Recycled Contents	100% Virgin Vinyl	
Backstamp info	None	
CE Certification	Yes	
<b>PACKING SPEC'S</b>	<b>DETAILS</b>	<b>ADDITIONAL INFORMATION</b>
	6" x 48"	
Product dimension (Width, mm)	150mm	
Product dimension (Length, mm)	1200mm	
Pallet Dimensions (L x W x H)	1260 x 1010 x 770mm	
Square feet per plank/tile [formula field]	1.94	
Square feet per carton	52.31	
Square feet per pallet	3138.78	
Square feet per container [formula field]	50220.52	20 foot container
Weight per sq ft(lbs) [formula field]	0.77	
Weight per plank/tile (lbs/plank)	1.49	
Weight per carton (lbs)	40.17	
Weight per pallet (lbs)	2410.09	
Weight per container (lbs)	38561.50	
Pieces per box	27	
Boxes per pallet	60	
Box Type	U	
Pallet per container	16	
Boxes per container [formual field]	960	
<b>PRODUCT PERFORMANCE / TESTING</b>	<b>PERFORMANCE</b>	<b>ASTM REQUIREMENT</b>
ASTM F2055 Size and Tolerance	Passes	As speicified 0.016 in./lin.ft
ASTM F386 Thickness	Passes	As speicified 0.005 in./lin.ft
ASTM F2055 Squareness	Passes	Max. 0.010 in.
ASTM F1914 Residual Indentation	Passes	Avg. < 8%
ASTM F137 Flexibility	Passes 6mm mandrel	1 in (25.4mm) mandrel / no crack or break
ASTM F2199 Dimension Stability	Passes	<0.020in./ft
ASTM F925 Chemical Resistance	Passes	No change/Slight change
ASTM F1514 Resistance to Heat	Passes	< 8 (delta E) avg.
ASTM F1515 Resistance to Light	Passes	< 8 (delta E) avg.
ASTM E648 Critical Radiant Flux	Class 1	Class 1 (<0.45 W/σ <sup>2</sup> )
ASTM E662 Optical Smoke Density	Passes	< 450
ASTM C1028 Slip Resistance	Passes	ADA Compliant(> 0.50)
ASTM F970 Static Load	2000 psi	250 psi(< 0.005")
<b>TECHNICAL INFORMATION / DOCUMENTS</b>	<b>DETAILS</b>	<b>ADDITIONAL INFORMATION</b>
Product Warranty	10 years for Light Commercial/ 25 years Residential	
Installation Method	Full spread	
Approved Installation Methods	Above, Below, and On-Grade	
Recommended Adhesive(s)	Any approved LVT adhesive	
Polished Required (Y/N)	None	