

# H·FLOR

## WoodHaven

**LX Hausys America, Inc.**

3480 Preston Ridge Rd. Suite 350

Alpharetta, GA 30005

866-544-4622

www.lxhausys.com

<b>COLLECTION NAME</b>	<b>WoodHaven</b>
<b>TOTAL # SKUs (Colors)</b>	<b>12</b>

PRODUCT SPECIFICATIONS/CONTENT/CERTIFICATIONS	DETAILS	ADDITIONAL INFORMATION
Thickness	5.0 mm (0.197")	1.0 mm (0.039") IXPE foam
Wear Layer	20 mil (0.5 mm)	
Glass Fiber	No	
Finishing/Coating	Anti-microbial UV coating	
Nominal Dimensions (inches)	9" x 60"	
Actual Dimensions (mm)	232 mm x 1,532 mm	
Beveled	Yes, Painted bevel on 4 sides	
Class/ASTM F3261	Class I - Type B (embossed), Grade 1, Backing Class B	
Backing	IXPE Foam	
Gloss Level	5 - 8	
Classification	Residential / Commercial	
Added Antimicrobial	Yes, Coating	
Recycled Contents	100% Virgin Vinyl	
Backstamp Info	Yes	

PACKING SPECIFICATIONS	DETAILS	ADDITIONAL INFORMATION
Product Dimensions (W x L)	232 mm x 1,532 mm	
Pallet Dimensions (L x W x H)	1,570 mm x 1,010 mm x 581.6 mm	
Square feet per Plank	3.83	
Square feet per Box	26.781	
Square feet per Pallet	1,178.35	
Square feet per Container	23,566.91	20 ft. container
Weight per sqft (lbs.)	1.76	
Weight per Plank (lbs.)	6.72	
Weight per Box (lbs.)	47.01	
Weight per Pallet (lbs.)	2,130.00	
Weight per Container (lbs.)	42,592.00	
Pieces per Box	7	
Boxes per Pallet	44	
Box Type	Corrugated	
Pallet per Container	20	
Boxes per Container	880	

PRODUCT PERFORMANCE/TESTING	PERFORMANCE	ASTM REQUIREMENT
ASTM F2421 Size and Tolerance	Passes	± 0.080"
ASTM F387 Thickness	Passes	As specified ± 0.008" (with backing)
ASTM F2421 Squareness	Passes	Max. 0.010"
ASTM F1914 Residual Indentation	Passes	Avg. ≤ 0.007" (0.18 mm)
ASTM F2199 Dimension Stability	Passes	< 0.2% / lin.ft. (305 mm)
ASTM F2199 Curl	Passes	Max. 0.080" (2 mm)
ASTM F1914 Surface Integrity	Passes	No puncture through wear layer / deco into rigid core
ASTM F925 Chemical Resistance	Passes	Slight change only
ASTM F1514 Resistance to Heat	Passes	ΔE ≤ 8 avg. max
ASTM F1515 Resistance to Light	Passes	ΔE ≤ 8 avg. max
ASTM E648 Critical Radiant Flux	Class 1	Class 1 (< 0.45 watts/cm <sup>2</sup> )
ASTM E662 Optical Smoke Density	Passes	< 450 (under non-flaming exposure)
ASTM C1028 Slip Resistance	Passes	ADA Compliant (> 0.50)
ASTM F970 Static Load	Passes	≤ 0.005 in. (250 psi)

TECHNICAL INFORMATION/DOCUMENTS	DETAILS	ADDITIONAL INFORMATION
Product Warranty	10-Year Light Commercial / Lifetime Residential*	
Installation Method	Click	i4F
Approved Installation Locations	Above, Below, and On-Grade*	
Recommended Adhesive	None	
Polish Required (Y/N)	No	

\*The warranty covers manufacturing defects and wear-out in the ordinary exercise of due care.

\*All specifications are subject to change without notice.

