

Borealis

PRODUCT SPECIFICATIONS



Physical Construction	
Construction	Wood Fiber Based Flooring
Size	8.03" Wide x 47.64" Long
Overall Thickness	10mm (8mm plank + 2mm attached pad)
Pieces Per Carton	7 Planks
Coverage Per Carton	1.728m ² / 18.60 sq. ft.
Weight Per Carton	12.42kg / 27.38 lbs
AC Wear Rating	AC3

Testing	
Sound Transmission Class (ASTM E90, E413)	152mm slab, drop ceiling, STC60
Impact Insulation Class IIC (ASTM E429, E989)	152mm slab, drop ceiling, IIC63
Large Ball Impact Resistance (NALFA LF-01)	_1000mm
Small Ball Impact Resistance (NALFA LF-01)	_200mm
Cleanability / Stain Resistance (NALFA LF-01)	Score < 20 - No More Than Slight Effect
Light Resistance (NALFA LF-01)	No More Than Slight Effect
Wear Resistance (NALFA LF-01)	AC3; \geq 2,000 cycles
Thickness Swell (NALFA LF-01)	\leq 16%

Environmental

California CARB 93120 Phase 2
Compliant TSCA Title VI Compliant
GreenGuard Gold Certified

Warranty

25-Year Residential

Installation Method

Angle / Tap

